

PVC Suction & Discharge Hose

Product Datasheet



Technical Specification

1. Description

Clear PVC Spiral Food Quality Suction and Discharge Hose. Non-Phthalate, Reg. 2002/72/EC

2. Applications:

Suction and discharge of dry and a wide range of liquid food products.

3. Tube

PVC

4. Cover

PVC

5. Reinforcement

Rigid PVC spiral

6. Temperature

-15 Deg C to +65 Deg C

7. Vacuum

570mm Hg = 75% at 20°C

8. Coil Size

30 mtrs

9. Colour

Clear with White Spiral

Inside Diameter (mm)	Inside Diameter (inch)	Wall Thickness (mm)	Outside Diameter (mm)	Maximum working Pressure		Bend Radius (mm)	Weight (kg's/mtr)	CMT Part Number
				(23°C ± 2°C)	(55°C ± 2°C)			
25	1	3.30	31.6	7.3 bar	2.1 bar	100	0.38	0308005
32	1 ¼	3.43	38.9	5 bar	1.5 bar	115	0.49	0308010
38	1 ½	3.56	45.1	5 bar	1.5 bar	150	0.60	0308015
51	2	4.32	59.6	5 bar	1.5 bar	255	0.96	0308020
63	2 ½	5.57	72.1	5 bar	1.5 bar	300	1.25	0308025
76	3	5.08	86.2	4 bar	1.3 bar	355	1.65	0308030
102	4	5.84	113.7	3 bar	1 bar	400	2.52	0308035