

Fire Brigade Layflat Hose

Product Datasheet



Technical Specification

- 1. Description**
Type 3 Red (Fully coated Rubber Layflat) BS6391:2009 Type III

2. Applications:
Heavy duty multi-purpose layflat hose for all fire fighting applications.High abrasion, ozone and weathering resistance. Also suitable for salt water,oil and many chemicals.

3. Tube
Nitrile/PVC Compound

4. Cover
Nitrile/PVC Compound

- 5. Construction**
Circular woven jacket, one piece extrusion through the weave process

6. Temperature
- 35°C to +100°C

7. Coil Size
To customers requirements

8. Colour
Red

Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Vacuum HG		Bend Radius	Weight	CMT Part Number
(mm)	(inch)	(mm)	(inch)	(psi)	(bar)	(psi)	(bar)	(mm)	(inch)	(mm)	(kg's/mtr)	
38	1 ½	-	-	250	17	725	50	-	-	-	0.31	0360002
45	1 ¾	-	-	250	17	725	50	-	-	-	0.34	0360004
52	2	-	-	250	17	725	50	-	-	-	0.41	0360008
64	2 ½	-	-	250	17	725	50	-	-	-	0.58	0360010
75	3	-	-	250	17	725	45	-	-	-	0.70	0360012
100	4	-	-	220	15	580	40	-	-	-	0.85	0360014