

Sand & Shotblast Hose

Product Datasheet



Technical Specification

1. Description

Sand & Shotblast Hose to ISO 4649
Antistatic rubber compound

2. Applications:

Antistatic abrasion resistant hose for steel shot
And sand blasting in cleaning of finishing
metal, stone, glass or other surfaces.

3. Tube

SBR/NR Antistatic

4. Cover

Synthetic Rubber Antistatic

5. Reinforcement

Synthetic fabric plies

6. Temperature

From -40 Deg C to + 80 Deg C

7. Coil Size

20 or 40 metre coils

8. Colour

Black

Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Vacuum HG		Bend Radius	Weight (kg's/mtr)	CMT Part No.
(mm)	(inch)	(mm)	(inch)	(psi)	(bar)	(psi)	(bar)	(mm)	(inch)	(mm)		
12.70	1/2	29.00	1.14	180	12	630	42				0.49	1063005
19.05	3/4	33.00	1.30	180	12	630	42				0.64	1063007
19.05	3/4	36.00	1.42	180	12	630	42				0.80	1063010
25.40	1	39.00	1.54	180	12	630	42				0.78	1063015
25.40	1	48.00	1.89	180	12	630	42				1.50	1063020
31.75	1.1/4	48.00	1.89	180	12	630	42				1.11	1063025
38.10	1.1/2	60.00	2.36	180	12	630	42				2.01	1063035
38.10	1.1/2	56.50	2.22	180	12	630	42				1.50	1063045